

IR BULLET CAMERA, ALL-IN-ONE SOLUTION

*DC Auto Iris Varifocal Lens 9-22mm / ø5 IR LEDs*30pcs



OR-P501



GENERAL FEATURES

- 1/3" COLOR SONY Super HAD CCD II
- 40M range visible in total darkness with 30pcs of IR LEDs
- Supreme Resolution (600TV-Line : Color, 680TV-Line : B/W)
- Weather-proof(IP65)
- 3-Axis Bracket for 3D(Pan/Tilt/Roll) rotation
- Day & Night function(ICR)
- Split Glass Technology
- Using IR Lens to prevent defocusing. (F1.2)
- Option : 12V DC or 24V AC Dual voltage

SPECIFICATIONS

Image Sensor	1/3" COLOR SONY SUPER HAD CCD II
Pixel	410K
Scanning System	2:1 Interlace
Sync. Type	Internal PAL
Resolution	600 TV-LINE(COLOR), 680 TV-LINE(B/W)
S/N Ratio	48dB or More(AGC OFF)
Video Output	1.0 Vp-p(Sync. Negative) Termination 75Ω
Min. Illumination	0.01 Lux(F/1.2), 0 Lux (40M Range at LED HIGH) : Indoor
Gamma	γ=0.45 typ.(0.45, 0.6, 1.0, user)
OSD	Yes(Multi Language)
White Balance	ATW(2,500°K~9,500°K)/MANUAL/AWC
Shutter Speed	1/50 ~ 1/100,000sec
Backlight	BLC/HLC/OFF
AGC	LOW/MIDDLE/HIGH/OFF
Motion Detection	ON/OFF (64 Block)
Privacy Zone	ON/OFF (4 Zone)
Mirror	ON/OFF
Day & Night	ICR(AUTO, COLOR, B/W)
LED	30pcs
Impact Detection	LOW/MIDDLE/HIGH/OFF
Communication	RS-485(Protocol : Pelco D, Pelco P)
Lens	9-22mm Vari-focal auto iris lens
Power Supply	12V DC or 24V AC(Dual Voltage) - Option
Current Consumption	MAX. 600mA(at 12V DC) : LED ON
Fan	Option
Operation Temp.	-20°C ~ 50°C
Preservation Temp.	-20°C ~ 60°C
Dimension	79(W) X 80.5(H) X 172.3(D) mm
Weight	Approx. 1.5Kg

DIMENSIONS

